



L3HARRIS®
FAST. FORWARD.

XL ONBOARD™ 85 MOBILE

Single-Band 700/800 MHz Mobile Radio

The L3Harris XL Onboard 85M mobile radio is a feature-rich, cost-effective option for reliable, mission-critical communications. With P25 Trunking, Phase 1 and Phase 2 capabilities, this radio is outstanding for first responders and utility customers who need to manage their migration needs with just one device.

The ride is always smoother with a best-in-class radio by your side. The XL Onboard Series P25 radios bring unflinching critical communications to any vehicle in your fleet. Connect in more ways than ever with Wi-Fi, Bluetooth®, and GPS capabilities. Let's go.

RELENTLESSLY RELIABLE

XL Radios run on systems that double down on redundancy, champion open networks and connect seamlessly with P25-compliant organizations.

POINT-TO-POINT SECURE

Our AES-256 encryption provides an end-to-end secure configuration, keeping you safe from threats.

BACKED WITH ALL-IN, 24/7 SUPPORT

Our service packages keep your radios up and running with in-field preventative maintenance and software upgrades.

Key Benefits:

- > Interoperability across 700/800 MHz bands
- > Connects in more places with Wi-Fi, Bluetooth and GPS
- > Wi-Fi enabled voice and device management
- > Multiple encryption options for secure communications
- > Modular design for flexible mounting configurations
- > Advanced noise cancellation technology
- > Ruggedized to MIL-STD-810H standards for tough conditions
- > 2.4-inch color display with six programmable buttons and simple menu access



SPECIFICATIONS FOR: XL ONBOARD 85 MOBILE RADIO

GENERAL	
Dimensions (H x W x D): (Excludes knobs)	Size: 62mm x175mm x 238mm (Excluding protrusions)
Weight (without brackets)	6.5 lbs (2.95 kg)
Channel/Talkgroup Capacity	12,500 (1,250 per mission plan; up to 10 mission plans)
Radio Programming	Firmware, personalities and feature sets through USB or via Wi-Fi
Control Unit	18-bit color LCD 320 pixels x 240 pixels 2.4-inch color LCD with up to 3 lines of text, status bar and menu buttons Three programmable menu/option buttons and three additional programmable buttons Separate volume and channel selector knobs Single DIN sizing One USB Type-C port for microphone
Speakers: External, 15 W	One 15W audio channel on the radio control head and one on the radio body, with less than 3% distortion
Environmental Specifications: Relative Humidity Operating Temperature Storage Temperature Ambient Temperature Range Altitude: Operational In-Transit	90% @ 122°F (+50°C) -22°F to +140°F (-30°C to +60°C) -40°F to +176°F (-40°C to +80°C) -22°F to +140°F (-30°C to 60°C) 15,000 ft (4,572 m) 50,000 ft (15,240 m)
Electrical: System Voltage Standby Current Drain Receive Current Drain Current Drain @ 35W TX	10.88 to 16.32 VDC negative ground 1A 2A 10A nominal
GPS/GNSS: Channels GNSS Constellations Supported Tracking Sensitivity Acquisition Sensitivity Cold Start Hot Start Feature	P25 standard TIER 2 and L3Harris in-band 52 2 -165 dBm (GPS), -163 dBm (GLONASS) -146 dBm (GPS) < 35 seconds < 1 second

LMR TRANSMITTER	
Frequency Bands (MHz)	700/800
Frequency Range (U.S.)	768-776, 798-806, 806-816, 851-861
Frequency Range (Int'l)	763-776, 793-806, 806-825, 851-870
Modulation Limiting (kHz)	2.5, 4, or 5 FM
Audio Response	Meets TIA-603-D Section 3.2.6
Spurious and Harmonics (dBc)	< -75, FCC Part 90
FM Hum and Noise (dB @ 12.5 kHz)	45.0
FM Hum and Noise (dB @ 25 kHz)	47.0
Audio Distortion (%)	< 1.0
P25 Modulation Fidelity (%)	< 3.00
Frequency Stability (ppm)	±1.5
P25 Adjacent Power (dB)	> 67
Channel Spacing (kHz)	12.5, 25
Conducted Emissions (dBc)	-75
Radiated Emissions	Meets TIA/EIA-603-D 3.2.12

SPECIFICATIONS FOR: XL ONBOARD 85 MOBILE RADIO

LMR RECEIVER	
Frequency Bands (MHz)	700/800
Frequency Range (U.S.)	768-776, 851-861
Frequency Range (Int'l)	763-776, 851-870
Channel Spacing (kHz)	12.5, 25
Sensitivity (12 dB SINAD)	-119 dBm
P25 Sensitivity (5% BER)	-119 dBm
Adjacent Channel Rejection @ 25 kHz (dB)	70
Adjacent Channel Rejection @ 12.5 kHz (dB)	64
P25 Adjacent Channel Rejection @ 12.5 kHz (dB)	60
Intermodulation Distortion (dB)	76
FM Hum and Noise @ 12.5 kHz (dB)	45
FM Hum and Noise @ 25 kHz (dB)	47
Rated Audio Output	1 channel of 15W RMS into 4 Ohm
Audio Distortion	< 3.0% @ rated power
Stability Rejection (ppm)	+/- 1.5
Spurious Rejection (dB)	88
Selectivity (dB)	20 (NPSAC Only)

BROADBAND	
Wi-Fi	802.11 b/g/n 2.4 GHz and 5 GHz; supports 24 preconfigured and 8 user configured networks
Bluetooth	Bluetooth 4.0 (128-bit encryption)

ENVIRONMENTAL STANDARD			
Applicable Standard	Parameter	Methods	Procedure/Categories
MIL-STD-810H	Low Pressure	500.6	1, 2
	High Temperature	501.7	1, 2
	Low Temperature	502.7	1, 2
	Temperature Shock	503.7	1-B
	Contamination by Fluids	504.3	2
	Solar Radiation	505.7	2
	Blowing Rain	506.6	1
	Humidity	507.6	2
	Salt Fog	509.7	1
	Blowing Dust	510.7	1
	Blowing Sand	510.7	2
	Vibration (Basic Transportation)	514.8	1, Category 4
	Vibration (Minimum Integrity)	514.8	1, Category 24
	Functional/Basic Shock	516.8	1
	Shock (Crash Hazard)	516.6	6
	Shock (Bench Handling)	516.6	6
Transit Drop	516.8	6	
U.S. Forest Service	Vibration Stability (10-60 Hz)	Paragraph 2.15	
IEC 60529	Dust-tight and Water Jets	IP65 (Control Unit) IP54 (Radio)	Table 2, Par. 13.4 Table 3, Par. 14.2.5

*Also meets equivalent superseded MIL-STD-810D, E, F, and G

SPECIFICATIONS FOR: XL ONBOARD 85 MOBILE RADIO

DIGITAL OPERATION		(Continued from previous page)
Protocol	P25	ProVoice™
Vocoding Method	AMBE+2™ Enhanced Full Rate & Enhanced Half Rate	AMBE+2™ Enhanced Full Rate
Signaling Rate (kbps)	9.6	9.6
Modulation	Phase 1 TX: C4FM, RX: C4FM & CQPSK Phase 2 TX: HCPM, RX: HDCQPSK	GFSK
L3Harris Failsoft Operation	Switch to site Trunking Mode (for L3Harris infrastructure) or P25 Conventional Failsoft for Motorola	

ENCRYPTION	
Encryption Algorithms	Voice Encryption: Single-key AES/DES, Multiple-key AES/DES, DES-OFB, Encryption Lite (ARC4), 256-bit AES P25, 64-bit DES Control Channel Encryption: 128-bit AES (LLA)
Encryption Keys Per Radio	Number of Encryption Keys per Keystore (up to 5 keystores per radio): 128 AES, 64 DES, 5 LLA, 8 Encryption Lite (ARC4), 4 AES UKEK, 4 DES UKEK
Keying	L3Harris Key Loader, P25 Over-the-Air-Rekeying (OTAR), Motorola KVL 3000+/4000/5000
Standards	FIPS 140-2 Level 1, FIPS 197

REGULATORY DATA						
Frequency Range	RF Output (W)	Frequency Stability	FCC Type Acceptance ID	Applicable FCC Rule	Industry Canada ID	Applicable Industry Canada Rule
763-776, 793-806	30.0	1.5	OWDTR-0170-E	90	3636B-0170	RSS-119
806-825, 851-870	35.0	1.5	OWDTR-0170-E	90	3636B-0170	RSS-119
Emissions Designators	16K0F3E, 16K0F1D, 16K0F1E, 14K0F3E, 14K0F1D, 14K0F1E, 11K0F3E, 11K7F1D, 11K7F1E, 8K40F1D, 8K40F1E, 8K10DXW, 18K5F1W, 12K9F1W					

ACCESSORIES	
Microphone:	Tough, ergonomic digital microphone enabling noise cancellation.
Keypad Mobile Microphone:	Rugged microphone equipped with a 12-button keypad and 5-way controller for radio control and noise cancellation in the palm of the user's hand.
XL-RHHC:	The XL-Mobile Ruggedized Handheld Controller has the same functions as the XL Onboard control head, with a full-color LCD screen, mobile microphone and alphanumeric keypad in a compact unit.
Desktop Cabinet:	Supports desktop deployment of the XL mobile radio in front-mount, remote mount and control head-only configurations.
External Speaker:	Compact and carefully tuned for the human voice, the XL 85M external speakers deliver loud and clear mission-critical audio in an easy-to-mount enclosure.

Technical specifications are subject to change without notice.
Product sales are subject to applicable U.S. export control laws.

XL Onboard 85M, Single-Band Mobile Radio

© 2024 L3Harris Technologies, Inc. | 4/2024 DS705B

Non-Export Controlled Information. These item(s)/data have been reviewed in accordance with the International Traffic in Arms Regulations (ITAR), 22 CFR part 120.34 and the Export Administration Regulations S (EAR), 15 CFR 734(3)(b)(3), and may be released without export restrictions.

L3Harris Technologies is the Trusted Disruptor in the defense industry. With customers' mission-critical needs always in mind, our 50,000 employees deliver end-to-end technology solutions connecting the space, air, land, sea and cyber domains in the interest of national security.



1025 W. NASA Boulevard
Melbourne, FL 32919

L3Harris.com